



PERMANON · USA™
INNOVATIVE SURFACE PROTECTION



Application Instructions

1. Clean the surface to be protected.

• We highly recommend cleaning the surface with Extreme Simple Green Aircraft Cleaner. It is a superb Ph Balanced product that is economical, sold as a concentrate, and conforms to Boeing Aircraft requirements for application to all exterior surfaces.

• Other Ph balanced cleaners may be used provided they DO NOT have silicone, wax, oil, or petroleum/other additives that leave any residues.

2. Mix a 5-10% solution of Permanon into a clean sprayer. The clear cup cap on your Permanon bottle has measurement lines on it.



A simple 32 oz plastic spray head bottle will allow you to mix up a liter of solution. Pressure sprayers can be used as well (like ones from your local home and garden center or specialized units for industry or maintenance).

- As an example to mix up one liter of 10% solution:
- Fill the cap twice to the 50ml line on the cap (total of 100ml) and pour it into your spray bottle.
- Top off with water to your spray bottle's one liter mark. If your spray bottle does not have a one liter mark

add a generous 4 cups (32 oz) of water.

3. Lightly spray the Permanon 10% solution onto the surface to be treated (it is safe and effective on glass, metal, plastic, rubber, paint, varnish, polished stone, cultured stone, and any other solid surface).

4. Dry the surface.

• Use a micro-fiber cloth to dry treated surfaces. All water contains varying degrees of mineral deposits. If the surface is not dried completely it will water spot.

5. Step back and admire the results, you are done. No buffing, polishing, or other forms of "elbow grease"!

www.permanonusa.com/information.html
1-877-2947849 • info@permanonusa.com

